



TECHNICAL PAINT SERVICES

A174 CERAMIC TILE FINISH

Features:

A specially formulated, lead free, synthetic paint finish for ceramic tiles conforming to BS4310, exhibiting excellent heat, oil, petrol and water resistance. Not recommended for shower units or immersion under water.

Availability:

All BS4800 colours plus Black and White in a gloss finish in 5, 2.5 and 1 Litre containers.

Volume Solids:

55% ± 3% (BS 3900 Part A10).

Preparation:

The tiles must be de-glazed, thoroughly cleaned, dry and free from dust and grease.

Application:

By brush or conventional spray. Although supplied ready for use for brushing (although in cold conditions it may be necessary to thin with X156 White Spirit or ATR 154 Synthetic Brushing Thinner) thin, up to 25% by volume with UTR112 Universal Synthetic Thinners, to achieve a spraying viscosity of 25 - 30 seconds BSB4 cup @ 20°C. If more than one coat is required, allow first coat to dry overnight, lightly de-nib with fine abrasive paper, and apply a further coat. If a matt finish is required, this should be applied over a gloss finish.

Coverage:

40 sq metres per 5 Litres per coat @ 25 microns dry film thickness.

Drying:

Touch dry: 6 - 8 hours depending on temperature.

Recoatable: Overnight.

Drying time may be reduced by the addition of X21 Liquid Driers or Terebine Driers.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.