



TECHNICAL PAINT SERVICES

X163 CONCRETE ETCH CLEANER

Features:

A balanced acid solution specially formulated to prepare surfaces for painting. Removes surface laitance, neutralises excess alkalinity of newly laid concrete, reduces the likelihood of reaction where chemical cement hardeners have been used and provides key for painting. Also suitable for the removal of cement and plaster stains from brick or ceramic surfaces.

Availability:

5 Litre containers.

Volume Solids:

N/A.

Preparation:

The substrate must be thoroughly cleaned and free from dust and grease, using X14 Degreaser. If the surface appears to be very porous, it should be slightly dampened before application of X163.

Application:

Brush with a vigorous scrubbing action, which will cause the concrete to foam. When foaming stops, normally after 15 - 20 minutes, the concrete should be thoroughly washed down with clean water and allowed to dry completely before application of paint or sealer.

Coverage:

Approximately 20 sq metres per 5 Litres.

Drying:

N/A.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.